



# Palm Zire 72v1 Screen Replacement

This guide will demonstrate how to remove and replace a broken screen.

Written By: Celeste



## INTRODUCTION

Use this guide to replace a screen that is cracked or otherwise broken. Ensure that the problem can't be eliminated any other way, such as with a reset. See the [Zire72v1 Troubleshooting](#) page for other techniques to use on a faulty device.

---



### TOOLS:

- [MacBook Pro and Air 5-Point Pentalobe Screwdriver](#) (1)
  - [Phillips #000 Screwdriver](#) (1)
-

## Step 1 — Zire 72v1



- Power off your Zire 72 and turn the unit over.

## Step 2



- Remove the two screws on the bottom of the rear of the unit.

## Step 3



- Peel back the information sticker.
- Remove the one screw that connects the metal panel to the body of the Zire72.

## Step 4



- Use the tip of your screwdriver to pop the metal panel off the top of the rear of the unit to expose two more screws on the top corners.

## Step 5



- Remove the two top screws.

## Step 6



- Insert the tip of your screwdriver in the seam where the front frame meets the body of the unit and pry the frame up to pop it off. Remove it.



## Step 7



- Pull the back panel off the body of the unit to expose the motherboard in the body.

## Step 8



- Unplug the two orange ribbon cables at the top of the motherboard and remove the motherboard from the body. All that is left is the LCD screen in the front housing of the unit.

## Step 9



- Remove the screen from the front housing and set it aside.

## Step 10



- Now that you have your Zire open, you can remove and replace the defective part.

## Step 11 — Screen



- Having successfully completed the Palm Zire72v1 Teardown, your device should now closely resemble this picture.
- The front and back panels should be separated and laid side-by-side.
- The front panel is on the left and contains the screen and navigation buttons.
- The back panel is on the right and contains the circuit board and battery.

## Step 12



- To replace the screen, you will be working exclusively with the front (left) panel.



## Step 13



- Remove the old screen.
- Slide the screen upward and out of the plastic shell.
- The navigation panel may be removed if it interferes with screen replacement.

## Step 14



- Once the old screen is completely removed, you be left with the plastic shell.
- The new screen will be inserted into this case.

## Step 15



- The old screen will be entirely separate from the rest of the device.
- Dispose of this broken technology responsibly.
- You are now set to insert the new screen and reassemble the device.

---

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-09-05 08:48:36 PM.